

液态硅胶色浆

LSR Silicone Colorant

描述 Description

液态硅橡胶产品着色 LSR silicone rubber coloring

产品型号 Coloursoul Product Code: 19-1400

应用 Applications



加成型硅胶 Additional Silicone

缩合型硅胶 Condensation Silicone

技术参数 Technical parameters

性能 Properties	参数 Value	单位 Unit	测试方法 Method
颜色外观 Appearance	Blue Green	-	目视 Visual
建议添加比例 Suggested Dosage	1~3%	%	-
色差 D65 Color difference	<0.5	-	D65 CIE94
密度 Density	1.1±0.05	g/cm ³	ISO 1183
热稳定性 Heat Stability	300	°C	DIN EN 12877
耐光牢度 Light Fastness	8	grade	ISO 4892
黏度 Viscosity	26000±5000	mPa.s	ISO 1524
刮板细度 Grindometer	<15	μm	Grindometer

色板 Color Card

纯色 Solid	浅色 Light
	

使用方法及注意事项 Usage and precautions

过高地加入色浆可能会对硅橡胶的硬度及硫化产生一定的影响，请谨慎评估。

Over high adding ratio of colorant may affect the hardness or vulcanization of silicone, please evaluate the dosage carefully.

储存条件: 密闭存放于阴凉干燥通风处

Store Condition: Store in a cool, dry and ventilated place

包装规格: 20 Kg/桶

Package: 20 Kg/drum

保质期: 3年

Shelf Life: 3 Years

注：以上数据或描述基于凯乐兴目前仅有的认知或供应商提供的数据，用户有责任需自我验证产品的可靠性，是否满足产品要求,凯乐兴不做任何明示或暗示的保证。

Note: The above data or description is based on the current knowledge or supplier data provided by Colour soul, the user is responsible for self-verification of the reliability of the product, whether to meet the product requirements. Colour soul makes no warranty, express or implied.